

## Presse da parete

Articolo 7257




switched, with mechanical DUO-interlock, protected by 1 RCD 30 mA and 1 "K"-type MCB

## Specifiche tecniche

|                     |            |
|---------------------|------------|
| Corrente            | 63 A       |
| Poli                | 4 p        |
| Voltaggio           | 400 V      |
| Posizioni orologio  | 6 h        |
| Hertz               | 50-60 Hz   |
| Contatti            | X-CONTACT® |
| Grado di protezione | IP 67      |
| Materiale           | plastica   |
| Peso                | 4859 g     |

## Disegni e dimensioni



| Drawing    | Amp.  | 63   |      |      |
|------------|---|------|------|------|
| 1 MB 620   | Poles   | 3    | 4    | 5    |
| Dim. in mm | a   | 460  | 460  | 460  |
|            | b   | 180  | 180  | 180  |
|            | c   | 202  | 202  | 202  |
|            | d   | 440  | 440  | 440  |
|            | e   | 160  | 160  | 160  |
|            | f   | 8.1  | 8.1  | 8.1  |
|            | g   | 8    | 8    | 8    |
|            | h   | 505  | 505  | 505  |
|            | M   | 40   | 40   | 40   |
|            | M*  | 2x40 | 2x40 | 2x40 |
|            | Max. cable diam. (mm)   | 27   | 27   | 27   |
|            | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 6    | 6    | 6    |
|            |   | -25  | -25  | -25  |